


BroachingSert



Type: Broach



Type: BroachH (headed)



Broach/BroachH (headed)

Material Code

B = brass

General information

- Designed to cope with hard brittle thermoset materials.
- High torque resistance.
- Low bursting stress allows the use of thinner wall bosses reducing risk of sink marks.
- Self-aligning - assists installation.

How to order

Type + Thread+ Alt. Length (if applicable) + Material Code

Example: Broach-M5-B or BroachH-M4-B

Thread	L mm	B mm	C mm	K mm	N mm	Rec. Hole Size -0.00 / +0.10 mm	Min. Wall Thickness mm	Please note!
M2	4.1	0.51	4.8	3.3	3.0	3.1	1.6	
M2.5	5.3	0.58	5.5	4.2	3.7	3.8	2.0	
M3	5.3	0.58	5.5	4.2	3.7	3.8	2.0	
M3.5	6.3	0.74	6.4	5.0	4.5	4.6	2.5	
M4	7.4	0.89	7.1	5.8	5.3	5.4	2.5	
M5	8.3	1.07	7.9	6.6	6.1	6.2	2.5	
M6	9.2	1.32	9.5	8.2	7.7	7.8	2.8	
M8	9.2	1.32	11.1	9.7	9.3	9.3	3.8	
M10	9.2	1.57	14.0	12.7	12.2	12.3	5.0	